

AXALTA COATING SYSTEMS



General Industrial

Tufcote™ LV HG

MX-5500 Polyurethane Economy Products



Tufcote™ LV HG series polyurethane topcoat for the economy industrial market.

Tufcote LV HG MX-5500 topcoat are a two-component polyurethane designed to provide a high gloss, extremely durable, solvent- and chemical-resistant coating. This economy segment, industrial maintenance coating is formulated with a volatile organic compound (VOC) of 0.8 lbs/gal (100 g/l) to meet the strict requirements of SCAQMD Rule 1113. The fast drying attributes of this topcoat allow for a quicker re-coat time over a variety of substrates in harsh corrosive environments.

Ultra Low VOC Solventborne Coatings

Tufcote LV HG Series MX-5500 Polyurethane Topcoat

(Formerly Maximus MX-5500 Series)

A two-part, high-quality polyurethane for use on steel and wood designed to provide an extremely durable solvent- and chemical-resistant topcoat with exceptional resistance to chipping and abrasion.

Available as a kit with MX-5599 Polyurethane Activator, this coating delivers exceptional durability and protection, and a high gloss finish.

Color offering includes:

MX-5500 White

MX-5501 Black

May be applied by spray application, brush or roller.

MX-5500 Urethane Topcoat is recommended for use over:

Tufcote LV PR 5187 Epoxy Primer

(Formerly Maximus 5187 Series)

This corrosion-resistant light grey two-part epoxy primer is extremely hard, tough and durable. When mixed with Tufcote 5199 Activator, the combined components deliver exceptionally strong adhesion and excellent long-term protection at a VOC level of 0.8 lbs/gal (100 g/l), or less, to meet the requirements of SCAQMD Rule 1113 for the category of Industrial Maintenance Coatings.

May be applied by spray application, brush or roller.

Target Industries

- » Oil refineries
- » Off-shore platforms
- » Storage tanks
- » Steel
- » Machinery
- » Structural steel
- » Piers

Substrates

- » Ferrous metals
- » Wood
- » Concrete
- » Painted surfaces

Product Attributes

- » Exceptionally strong adhesion
- » Long-term protection
- » Chemical resistance
- » Exceptional resistance to chipping and abrasion
- » Easy mixing



Available at **blendsupply.com**

1.800.647.9279

orders@blendsupply.com

Contact us.

1.855.6.AXALTA
axalta.us

Copyright © 2017 Axalta Coating Systems and all affiliates. All rights reserved.
E-R5906 09/17



BLEND SUPPLY

DISTRIBUTOR OF COATINGS, TOOLS & REFINISH SUPPLIES

