

AXALTA COATING SYSTEMS



BLEND SUPPLY

General Industrial

Tufcote™ LV HG

5100 Epoxy Economy Products



Tufcote™ LV HG series epoxy products for the economy industrial market.

Tufcote LV HG series epoxy topcoat is a two-component, heavy duty thixotropic high gloss coatings, catalyzed with a unique activator. Epoxy coatings are known for their toughness and strong adhesion characteristics. This economy coating is extremely hard, tough and durable for use indoors, outdoors, and over properly prepared substrates for above water exposure. When mixed with Tufcote 5190 Epoxy Activator, the volatile organic compound (VOC) level of the combined components is formulated at 0.4 lbs/gal (50 g/l), or less. The extremely low VOC helps reduce environmental impact.

Ultra Low VOC Solventborne Coatings

Tufcote LV HG Series 5100 Epoxy Topcoat

(Formerly Maximus 5100 Series)

When mixed with 5190 Epoxy Activator in a simple 4:1 mix ratio, this coating is formulated to deliver exceptional durability, protection and a very high gloss finish.

Color offering includes:

51844W White

5101 Black

5107 Light Grey

May be applied by spray application, brush or roller.

5100 Epoxy Topcoat is recommended for use over:

Tufcote LV PR 5187 Epoxy Primer

(Formerly Maximus 5187 Series)

This corrosion-resistant light grey two-part epoxy primer is extremely hard, tough and durable. When mixed with Tufcote 5199 Activator, the combined component is designed to deliver exceptionally strong adhesion and excellent long-term protection at a VOC level of 0.8 lbs/gal (100 g/l), or less, to meet the requirements of SCAQMD Rule 1113 for the category of Industrial Maintenance Coatings.

May be applied by spray application, brush or roller.

Target Industries

- » Oil refineries
- » Off-shore platforms
- » Storage tanks
- » Steel
- » Machinery
- » Structural steel
- » Piers

Substrates

- » Steel
- » Wood
- » Concrete
- » Aluminum
- » Fiberglass

Product Attributes

- » Exceptionally strong adhesion
- » Long-term protection
- » Chemical resistance
- » Exceptional resistance to chipping and abrasion
- » Easy mixing



Available at **blendsupply.com**

1.800.647.9279

orders@blendsupply.com

Contact us.

1.855.6.AXALTA
axalta.us

Copyright © 2017 Axalta Coating Systems and all affiliates. All rights reserved.
E-R5907 09/17



BLEND SUPPLY
DISTRIBUTOR OF COATINGS, TOOLS & REFINISH SUPPLIES

